Rec'd PCT/PT9 06 MAY 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



! CERTA EXITATED O CORRES FORM CORRES CORRES ON THE FORM CORRES ON THE CORRESPONDING CORRESPONDING CORRESPONDING

(43) International Publication Date 21 May 2004 (21.05.2004)

PCT

(10) International Publication Number WO 2004/041059 A3

(51) International Patent Classification7:

A61B 5/03

(21) International Application Number:

PCT/IL2003/000928

(22) International Filing Date:

6 November 2003 (06.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

10/289,304


7 November 2002 (07.11.2002)

- (71) Applicant (for all designated States except US): TRIG MEDICAL LTD. [IL/IL]; POB 538, 36603 Nesher (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PALTIELI, Yoav [IL/IL]; 16 Sheerit Hapleta Street, 34987 Haifa (IL).

- (74) Agents: EITAN, PEARL, LATZER & CO-HEN-ZEDEK et al.; 2 Gav Yam Center, 7 Shenkar Street, 46725 Herzlia (IL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MONITORING THE PROGRESS OF LABOR



(57) Abstract: A method of monitoring the progress of labor in a mother during childbirth, by using a position sensor to measure a predetermined point on the mother; monitoring the location of the position sensor in three-dimensional space; and monitoring the location of the fetal presenting part with respect to the predetermined point on the mother. The location of the fetal presenting part may be indicated by a similar position sensor, or by imaging. Other conditions, such as effacement, cervical dilatation, and cervical position may also be monitored in a similar manner. A reference or affixation point may be provided to the position sensor by, for example, attaching a key or shaped object to one or more points on the fetus or mother.